

Electric Fryer

FEATURES:



- Stainless steel body makes it easy to clean and maintains hygiene.



- Built-in overheat protection device for safety (Manual restoration).
- Variety of choices to suit convenience stores or restaurants in terms of oil tank capacity and tank quantity for different models.



- Adjustable thermostat to control frying temperature.
- LED digital display clearly indicates time countdown, which is easy to read and control frying time. (Digital Type only)



Electric Fryer (Mechanical Type)



WFT-4L



WFT-8L



WFT-16L

Product Name	Model	Dimension(W*D*H)	Power	Temp. Range
4L Electric Fryer (Mechanical Type)	WFT-4L	207*406*290(mm)	220V 50Hz 2kW	Room Temp. to 200°C
8L Electric Fryer (Mechanical Type)	WFT-8L	297*414*290(mm)	220V 50Hz 3kW	Room Temp. to 200°C
16L Electric Fryer (Mechanical Type)	WFT-16L	585*415*290(mm)	220V 50Hz 3kW*2	Room Temp. to 200°C

Electric Fryer (Digital Type)



WFT-8L-C4



WFT-16L-C8

Product Name	Model	Dimension(W*D*H)	Power	Temp. Range
8L Electric Fryer (Digital Type)	WFT-8L-C4	306*412*310(mm)	220V 50Hz 3kW	Room Temp. to 200°C
14L Electric Fryer (Digital Type)	WFT-16L-C8	550*412*310(mm)	220V 50Hz 3kW*2	Room Temp. to 200°C

Standing Electric Fryer

FEATURES:



- Digital control system with one-button-pressing for automatic frying operation.
- Each tank is able to set 6 different kinds of food's timing from its respective channel and can work simultaneously.
- Easy frying by independent control panel with 12-channel timer.



- Built-in overheat protection device for safety. When oil temperature exceeds the set temperature, the power will be cut off. (Manual restoration).
- Easy cleaning with lift-up heating element.



- Use "all-in-one-button" frying operation program, frying basket will lift up automatically. This function is especially efficient for user during rush hours to avoid improper frying time. (For the fryer with auto lift-up system only)



- With innovative Y-shaped oil pipeline system, pipeline residual oil cleaning device and multiple anti-clogging devices.



WEL-1L



WEL-1L



WEL-2L



WEL-3L

Product Name	Model	Dimension(W*D*H)	Power	Capacity	Temp. Range
28L Electric Standing Fryer	WEL-1L	400*800*935/1160(mm)	380V 3N~ 50Hz 15.2kW	28L	Room Temp. to 190°C
56L Electric Standing Fryer with Filtration	WEL-2L	800*800*935/1160(mm)	380V 3N~ 50Hz 15.2kW*2	28L*2	Room Temp. to 190°C
84L Electric Standing Fryer with Filtration	WEL-3L	1200*800*935/1160(mm)	380V 3N~ 50Hz 15.2kW*3	28L*3	Room Temp. to 190°C
28L Electric Standing Fryer (twin tanks)	WEL-1L-2	400*800*935/1160(mm)	380V 3N~ 50Hz 7.6kW*2	28L	Room Temp. to 190°C
28L Electric Standing Fryer with Filtration	WEL-1LF	400*800*935/1160(mm)	380V 3N~ 50Hz 15.2kW	28L	Room Temp. to 190°C
28L Electric Standing Fryer With Filtration (Twin Tanks)	WEL-1LF-2	400*800*935/1160(mm)	380V 3N~ 50Hz 7.6kW*2	28L	Room Temp. to 190°C
28L Auto Lift-Up Electric Standing Fryer	WELL-1L	400*915*935/1464(mm)	380V 3N~ 50Hz 15.2kW	28L	Room Temp. to 190°C
28L Auto Lift-Up Electric Standing Fryer with Filtration	WELL-1LF	400*915*935/1464(mm)	380V 3N~ 50Hz 15.2kW	28L	Room Temp. to 190°C
28L Auto Lift-Up Electric Standing Fryer With Filtration (Twin Tanks)	WELL-1LF-2	400*915*935/1464(mm)	380V 3N~ 50Hz 7.6kW*2	28L	Room Temp. to 190°C

Electric Standing Fryer With Filtration



FEATURES:

- One-touch operation is easy to use, and all parts which contact the food are made of 304 stainless steel.
- 12 different times can be set, and the timing can be started at the same time.
- The button can set 10 different menus for each of the left and right slots. (LED)
- With 5.0-inch LCD touch screen plus key design. (LED)
- Self-contained oil filter system
- With shallow groove design, which reduces oil volume and energy consumption.
- It is Equipped with a temperature-limiting safety protection device, when the oil temperature exceeds the limit temperature, it can automatically cut off the power supply, which has the effect of over-temperature protection (manual reset).



AIWELL-1LF
AIWELL-1LF-2

AIWELL-1LF-S
AIWELL-1LF-2-S

AIWELL-2LF
AIWELL-2LF-3
AIWELL-2LF-4

AIWELL-2LF-S
AIWELL-2LF-3-S
AIWELL-2LF-4-S

Product Name	Model	Dimension(W*D*H)	Power	Capacity	Temp. Range
23L Electric Standing Fryer With Filtration	AIWELL-1LF	420*816*1145mm	3N ~ 380V 50Hz 15KW	23L	Room Temp. to 190°C
23L Electric Standing Fryer With Filtration (Twin Tanks)	AIWELL-1LF-2	420*816*1145mm	3N ~ 380V 50Hz 7.5KW*2	23L	Room Temp. to 190°C
45L Electric Standing Fryer With Filtration (Twin Tanks)	AIWELL-2LF	800*816*1145mm	3N~380V 50Hz 15KW*2	45L	Room Temp. to 190°C
45L Electric Standing Fryer With Filtration three tanks (one big tanks & two mall tanks)	AIWELL-2LF-3	800*816*1145mm	3N~380V 50Hz 15KW+7.5KW*2	45L	Room Temp. to 190°C
45L Electric Standing Fryer With Filtration (Four Small Tanks)	AIWELL-2LF-4	1180*816*1145mm	3N~380V 50Hz 7.5KW*4	45L	Room Temp. to 190°C
69L Electric Standing Fryer With Filtration (Three Tanks)	AIWELL-3LF-3	1180*816*1145mm	3N~380V 50Hz 15KW*3	69L	Room Temp. to 190°C
23L LED Display Electric Standing Fryer With Filtration	AIWELL-1LF-S	420*816*1145mm	3N ~ 380V 50Hz 15KW	23L	Room Temp. to 190°C
23L LED Display Electric Standing Fryer With Filtration (Twin Tanks)	AIWELL-1LF-2-S	420*816*1145mm	3N ~ 380V 50Hz 7.5KW*2	23L	Room Temp. to 190°C
45L LED Display Electric Standing Fryer With Filtration (Twin Tanks)	AIWELL-2LF-S	800*816*1145mm	3N~380V 50Hz 15KW*2	45L	Room Temp. to 190°C
45L LED Display Electric Standing Fryer With Filtration three tanks (one big tanks & two mall tanks)	AIWELL-2LF-3-S	800*816*1145mm	3N~380V 50Hz 15KW+7.5KW*2	45L	Room Temp. to 190°C
45L LED Display Electric Standing Fryer With Filtration (Four Small Tanks)	AIWELL-2LF-4-S	1180*816*1145mm	3N~380V 50Hz 7.5KW*4	45L	Room Temp. to 190°C
69L LED Display Electric Standing Fryer With Filtration (Three Tanks)	AIWELL-3LF-3-S	1180*816*1145mm	3N~380V 50Hz 15KW*3	69L	Room Temp. to 190°C

Electric Standing Fryer



FEATURES:

- Digital control system with one-button-pressing for automatic frying operation.
- Each tank is able to set 6 different kinds of food's timing from its respective channel and can work simultaneously.
- Easy frying by independent control panel with 12-channel timer.
- Built-in overheat protection device for safety. When oil temperature exceeds the set temperature, the power will be cut off. (Manual restoration).
- Easy cleaning with lift-up heating element.
- With innovative Y-shaped oil pipeline system, pipeline residual oil cleaning device and multiple anti-clogging devices.



23WEL-1LF
23WEL-1LF-2

23WEL-2LF
23WEL-2LF-3
23WEL-2LF-4

Product Name	Model	Dimension(W*D*H)	Power	Capacity	Temp. Range
23L Electric Standing Fryer	23WEL-1LF	420*816*1145mm	3N ~ 380V 50Hz 15KW	23L	Room Temp. to 190°C
23L Electric Standing Fryer (Twin Tanks)	23WEL-1LF-2	420*816*1145mm	3N ~ 380V 50Hz 7.5KW*2	23L	Room Temp. to 190°C
45L Electric Standing Fryer (Twin Tanks)	23WEL-2LF	780*816*1145mm	3N~380V 50Hz 15KW*2	45L	Room Temp. to 190°C
45L Electric Standing Fryer (One big tanks & two mall tanks)	23WEL-2LF-3	780*816*1145mm	3N~380V 50Hz 15KW+7.5KW*2	45L	Room Temp. to 190°C
45L Electric Standing Fryer (Four Small Tanks)	23WEL-2LF-4	780*816*1145mm	3N~380V 50Hz 7.5KW*4	45L	Room Temp. to 190°C
Electric Standing Fryer (Three Tanks)	23WEL-3LF-3	1140*816*1145mm	3N~380V 50Hz 15KW*3	69L	Room Temp. to 190°C